

Metric full nuts - Thread angle 60 degrees - Material acc. to ISO 898-2:2012

Thread dia.	Thread pitch			Width across flats		Width across corners	Depth	
	Coarse	Fine	Extra fine	min. mm	max. mm	min. mm	min. mm	max. mm
DIN 934								
M3	0.50	0.35	-	5.32	5.50	6.01	2.15	2.40
M4	0.70	0.50	-	6.78	7.00	7.66	2.90	3.20
M5	0.80	0.50	-	7.78	8.00	8.79	3.70	4.00
M6	1.00	0.75	-	9.78	10.00	11.05	4.70	5.00
M7	1.00	0.75	-	10.73	11.00	12.12	5.20	5.50
M8	1.25	1.00	0.75	12.73	12.00	14.38	6.14	6.50
M10	1.50	1.25	1.00	16.73	17.00	18.90	7.64	8.00
M12	1.75	1.50	1.25	18.67	19.00	21.10	9.64	10.00
M14	2.00	1.50	1.25	21.67	22.00	24.49	10.30	11.00
M16	2.00	1.50	1.00	23.67	24.00	26.75	12.30	13.00
M18	2.50	2.00	1.50	26.16	27.00	29.56	14.30	15.00
M20	2.50	2.00	1.50	29.16	30.00	32.95	14.90	16.00
M22	2.50	2.00	1.50	31.00	32.00	35.03	16.90	18.00
M24	3.00	2.00	1.50	35.00	36.00	39.55	17.70	19.00
M27	3.00	2.00	1.50	40.00	41.00	45.20	20.70	22.00
M30	3.50	2.00	1.50	45.00	46.00	50.85	22.70	24.00
M33	3.50	2.00	1.50	49.00	50.00	55.37	24.70	26.00
M36	4.00	3.00	2.00	53.80	55.00	60.79	27.40	29.00
M39	4.00	3.00	2.00	58.80	60.00	66.44	29.40	31.00
M42	4.50	3.00	2.00	63.10	65.00	71.30	32.40	34.00
M45	4.50	3.00	2.00	68.10	70.00	76.95	34.40	36.00
M48	5.00	3.00	2.00	73.10	75.00	82.60	36.40	38.00
M52	5.00	4.00	3.00	78.10	80.00	88.25	40.40	42.00
M56	5.50	4.00	3.00	82.80	85.00	93.56	43.40	45.00
M60	6.00	4.00	3.00	87.80	90.00	99.21	46.40	48.00
M64	6.00	4.00	3.00	92.80	95.00	104.86	49.10	51.00
M68	6.00	4.00	3.00	97.80	100.00	110.51	52.10	54.00
M72	6.00	4.00	3.00	102.80	105.00	116.16	56.10	58.00
M76	6.00	4.00	3.00	107.80	110.00	121.81	59.10	61.00
M80	6.00	4.00	3.00	112.80	115.00	127.46	62.10	64.00
M85	6.00	4.00	3.00	117.80	120.00	133.11	66.10	68.00
M90	6.00	4.00	3.00	127.50	130.00	144.08	70.10	72.00
M100	6.00	4.00	3.00	142.50	145.00	161.02	78.10	80.00
M110	6.00	4.00	-	152.50	155.00	172.32	85.80	88.00
M125	6.00	4.00	-	177.50	180.00	200.57	97.80	100.00
M140	6.00	-	-	195.40	200.00	220.80	109.80	112.00
M160	6.00	-	-	225.40	230.00	254.70	125.50	128.00

