

Metric lock nuts - Thread angle 60 degrees - Material acc. to ISO 898-2:2022

Thread dia.	Thread pitch			Width across flats		Width across corners	Depth	
	Coarse	Fine	Extra fine	min. mm	max. mm	min. mm	min. mm	max. mm
DIN 936								
M8	1.25	1.00	0.75	12.73	13.00	14.38	4.70	5.00
M10	1.50	1.25	1.00	16.73	17.00	18.90	5.70	6.00
M12	1.75	1.50	1.25	18.67	19.00	21.10	6.64	7.00
M14	2.00	1.50	1.25	21.67	22.00	24.49	7.42	8.00
M16	2.00	1.50	1.00	23.67	24.00	26.75	7.42	8.00
M18	2.50	2.00	1.50	26.16	27.00	29.56	8.42	9.00
M20	2.50	2.00	1.50	29.16	30.00	32.95	8.10	9.00
M22	2.50	2.00	1.50	31.00	32.00	35.03	9.10	10.00
M24	3.00	2.00	1.50	35.00	36.00	39.55	9.10	10.00
M27	3.00	2.00	1.50	40.00	41.00	45.20	10.90	12.00
M30	3.50	2.00	1.50	45.00	46.00	50.85	10.90	12.00
M33	3.50	2.00	1.50	49.00	50.00	55.37	12.90	14.00
M36	4.00	3.00	2.00	53.80	55.00	60.79	12.90	14.00
M39	4.00	3.00	2.00	58.80	60.00	66.44	14.90	16.00
M42	4.50	3.00	2.00	63.10	65.00	71.30	14.90	16.00
M45	4.50	3.00	2.00	68.10	70.00	76.95	16.90	18.00
M48	5.00	3.00	2.00	73.10	75.00	82.60	16.90	18.00
M52	5.00	4.00	3.00	78.10	80.00	88.25	18.70	20.00

